



UZ 13⁵/24⁵ UKUZ=+16.34

UZ 13⁵/24⁵ UKUZ=+16.34

UZ 13⁵/24⁵ UKUZ=+16.34

UKST=+16.34
UK BLEICH=+16.58⁵

BRH 0.15

BRH 0.15

BRH 0.15

BRH 0.15

QR_o 80*5mm

Diagonale Ø16mm, Riegel IPE 100

OR_o 80*5mm

F90

UZ 13⁵/24⁵ UKUZ=+16.34

WOHNUNG 9

BAU-NR.	4.2104	FLÄCHE	29.62qm
LH	2.50m	RH	2.50m
BD XX	WA XX	DE XX	

BAU-NR.	4.2103	FLÄCHE	12.71qm
LH	2.50m	RH	2.50m
BD XX	WA XX	DE XX	

BAU-NR.	4.2105	FLÄCHE	14.05qm (7.03)
LH	xxm	RH	xxm
BD XX	WA XX	DE XX	

BAU-NR.	4.2200	FLÄCHE	33.03qm
LH	2.50m	RH	2.50m
BD XX	WA XX	DE XX	

BAU-NR.	4.2100	FLÄCHE	32.26qm
LH	2.50m	RH	2.50m
BD XX	WA XX	DE XX	

BAU-NR.	4.2101	FLÄCHE	6.92qm
LH	2.50m	RH	2.50m
BD XX	WA XX	DE XX	

BAU-NR.	4.2102	FLÄCHE	3.22qm
LH	2.50m	RH	2.50m
BD XX	WA XX	DE XX	

60*40mm

BRH -0.07

BRH -0.07

DRAINROST

DRAINROST

FLACHDACHENTWASSERUNG, 1.5% GEFALLE

ATTIKA-ABLAUF Z.B. FA.LORO

TYP: KLEBEFLANSCH DN 100

RR Ø 100 AN GRUNDLEITUNG

Dg. BT C

WG 4.21

138⁵ 128¹